

SIZE	0.6Mpa		1.0Mpa		1.6Mpa	
	wet	dry	wet	dry	wet	dry
DN40	9.3	11.8	9.3	11.8	10.8	12
DN50	12.2	12.2	12.2	12.2	13	14
DN65	15.4	15.4	15.4	15.4	17.2	20.3
DN80	21.7	25.5	21.7	25.5	23	27.1
DN100	37.1	43.7	37.1	43.7	39.8	49.7
DN125	57.8	77.3	57.8	77.3	61.9	84.7
DN150	93.9	110.5	93.9	110.5	102.5	124.3
DN200	172.5	214.1	172.5	214.1	191.7	237.3
DN250	285.9	378	285.9	378	322.8	418
DN300	428.7	575.3	428.7	575.3	490.1	666.6
DN350	550.2	825.4	550.2	825.4	624.5	969.4
DN400	755.3	1132.9	755.3	1132.9	845.6	1306.8
DN450	1012.1	1518.2	1012.1	1518.2	1131	1787.3
DN500	1350.2	2025.3	1350.2	2025.3	1431.2	2307.7
DN600	2110.6	3165.8	2110.6	3165.8	2300.5	3710.4
DN700	3271.8	4907.8	3271.8	4907.8		
DN800	4307.4	6461.4	4307.4	6461.4		
DN900	5257	7885.4	5257	7885.4		
DN1000	8925	13387.6	8925	13387.6		
DN1200	12554	18831	12554	18831		

1. The safety factor is 1.5 when the pneumatic/hydraulic pressure is 8bar, and is 2 when the pneumatic/hydraulic pressure is 6bar

2. The safety factor is 1.5 when using electric actuator